

Technical data sheet

WorléeCryl[®] 7126

Art. No.: 332052-01544

Version: 02/2015

WorléeCryl 7126 is a medium particle size, high solids acrylic dispersion.

Technical Data:

Solid content	approx. 62 % +/- 1
pH	approx. 5,5 – 6,5
Density	approx. 1,05 g/cm ³
Viscosity	approx. 100 - 1000 mPas
Emulgent system	anionic
Min. film formation temperature	approx. 0°C
Glas transition temperature	approx. 8°C
Storage stability, 50°C	min. 30 days
Freeze-thaw-stability	protect from frost
Delivery form	approx. 62% in water

Application and properties:

WorléeCryl 7126 allows the formulation of clear caulks with an outstanding combination of rheology, adhesion and high solids using a single dispersion.

Outstanding Characteristics:

- high-elastic
- transparent in thick layers

Recommended storage conditions:

To ensure safe storage of WorléeCryl 7126, containers should be well sealed to prevent evaporation of water and the formation of skin on the surface. The emulsion must be stored at temperature above freezing. A temperature of +5 – +25°C for not more than six months is recommended. Higher temperatures will affect quality and cause the formation of crusts and skins, especially if the containers are not tightly closed or subjected to direct sunlight for long periods.