

Technical Leaflet

WorléeCryl L 2580

Art.-No. 112003-13162

Revision: 16.07.10

W´Cryl L 2580 is a neutral, physically drying, low odour acrylic resin, mainly for the use in wall and ceiling paints.

Technical Data:

Non volatile content, 1h/125 °C, DIN EN ISO 3251	70% ± 2
Viscosity, Rheometer, 23 °C, C 60/2°, 50 s ⁻¹	3,000 - 7,000 mPa·s
Acid value, on solids, DIN EN ISO 3682	max. 5 mg KOH/g
Colour, Gardner, delivery form, DIN ISO 4630	max. 1
Delivery form	70% in isoparaffin. HC 170 - 200

Solubility:

W´Cryl L 2580 is completely soluble or dilutable respectively in white spirit and isoparaffines (Isopar H, Isopar J - Exxon).

Application and Properties:

W´Cryl L 2580 is a soft acrylic resin. Additional plasticizers are not necessary.
W´Cryl L 2580 is especially suitable for the manufacture of wall and ceiling paints.

Wall paints based on W´Cryl L 2580 are of low odour and are isolating against water soluble nicotine, fume and chimney spots. Substrates sensitive against solvents like e.g. polystyrene are not attacked by decorative paints based on W´Cryl L 2580 and isoparaffines.